







BYD's Dream All Human Hope

Changing human dependence on non-renewable energy as the starting point, with three green dreams of electric vehicle, energy storage station and solar farm, BYD looks forward to helping more countries and people to get rid of fossil energy over consumption crisis and environmental pollution, and strive to leave offspring a beautiful and clean world to live in.

"

In the daytime, solar panels capture solar energy like plants. At night, energy storage station transports the stored energy, like solar energy, wind energy, tidal energy, to thousands of families smoothly.

The electric vehicle, shuttling on the streets and lanes, is of zero emission, zero pollution.

Is this a dream?

This is the green dream of BYD and even all human beings. Is this a dream?

No. We are already seeing it approaching us.

"







Average cell efficiency up to 19.0% Excellent optical performance



Power tolerance 0-5W Power Measurement Tolerance ±5% Reliability for output performance



12 years for product 25 years linear warranty



Residential roof top systems On/Off-grid commercial systems On/Off-grid utility systems



Design loads: 3600 Pa for positive (downward) and 1600 Pa for negative (upward) Safety factors Ym: 1.5

Corresponding to maximum snow and ice load 5400Pa, maximum wind load 2400Pa



IEC61215-1(ed.1)

IEC61215-1-1(ed.1)

IEC61215-2(ed.1)

IEC61730-1(ed.2)

IEC61730-2(ed.2)




BYD

Poly Half Cell Module

BYD PHK-36-SERIES-5BB 325-345W









BYD PHK-36-SERIES-5BB 325-345W

Mechanical Properties

Cell Type
Number of Cells
Dimension of Module
Weight
Front Glass
Frame
Junction Box
Cable Length
Connector

156.75×78.375mm
144
1992 mm×992 mm×35 mm
22.3 kg ±5%
3.2mm tempered glass with AR Coating
Anodized aluminum alloy
IP67(3 Diodes)
+320mm,-260mm(4.0mm²)
Genuine MC4 EVO2


Temperature Coefficient

Peak Power Temperature Coefficient
Open-Circuit Voltage Temperature Coefficient
Short-Circuit Current Temperature Coefficient

-0.349%/℃	
-0.285%/°C	
0.057%/°C	

Packing Information

Packing Type
Piece/Pallet
Pallet/Container
Piece/Container



Electrical Data (STC*)

Module Type
Rate Maximum Power (Pmax)(W)
Open Circuit Voltage (Voc) (V)
Short Circuit Current (Isc) (A)
Maximum Power Voltage (Vmp)(V)
Maximum Power Current (Imp) (A)
Module Efficiency %)

BYD325PHK-36	BYD330PHK-36	BYD335PHK-36	BYD340PHK-36	BYD345PHK-36
325Wp	330Wp	335Wp	340Wp	345Wp
44.94 V	45.19 V	45.44 V	45.69 V	45.94 V
9.140 A	9.196 A	9.252 A	9.308 A	9.364 A
37.57 V	37.83 V	38.10 V	38.36 V	38.62 V
8.654A	8.724 A	8.794A	8.864 A	8.934 A
16.45%	16.70%	16.95%	17.21%	17.46%

Standard Test Conditions (STC): irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

Electrical Data (NMOT*)

Module Type
Rate Maximum Power Pmax)(W)
Open Circuit Voltage (Voc) (V)
Short Circuit Current (Isc) (A)
Maximum Power Voltage (Vmp)(V)
Maximum Power Current (Imp) (A)

BYD325PHK-36	BYD330PHK-36	BYD335PHK-36	BYD340PHK-36	BYD345PHK-36
245.4Wp	248.9Wp	252.5Wp	256.0Wp	259.7Wp
42.3V	42.5V	42.7V	43.0V	43.2V
7.38A	7.43A	7.47A	7.52A	7.56A
35.0V	35.3V	35.6V	35.8V	36.2V
7.01A	7.06A	7.10A	7.14A	7.18A

Nominal Module Operating Temperature (NMOT): irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

Operational Parameter

Operating Temperature (°C)	-40°C~85°C
NMOT(Nominal Module operating temperature)	45°C±2°C
Maximum System Voltage (V)	1500(VDC)
Maximun Fuse Current Rating (A)	20A
Fire Safety	Class C
Power Tolerance	0~5W
Power Measurement Tolerance	±5%

BYD COMPANY LIMITED

ADD: No.1, Yan'an Road, Kuichong, Dapeng New Disctrict, Shenzhen, 518116, P.R.China





